The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

1. Identification of the substance/mixture and of the company/undertaking

Product identifier 1.1

Trade name: **ZF-LIFEGUARDFLUID 8**

Product code: S671.090.310

\$671.090.311 S671.090.312 S671.090.313

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Transmission oil.

Uses advised against: This product must not be used in applica-

> tions other than those listed in Section 1 without first seeking the advice of the

supplier.

Details of the supplier of the safety data sheet 1.3

ZF Friedrichshafen AG **ZF Aftermarket Obere Weiden 12** 97424 Schweinfurt Germany +49 9721 475 60 www.zf.com/contact

1.4 **Details of Australian Importer/Supplier**

ZF Services Pty Limited 14 Lidco Street Arndell Park NSW 2159 +61 2 9679 5555

1.5 **Emergency telephone number** 24/7h Emergency telephone number:

Australia ZF 24/7: Tel (+1) 300 938 324 (in English)

International GBK-EMETEL: Tel (+1) 352 323 3500 (in English)

+49 (0)89 19240 Information in German and English

ZF Friedrichshafen AG • ZF Aftermarket © ZF Friedrichshafen AG Obere Weiden 12, 97424 Schweinfurt, Germany

Phone: +49 9721 4756-0

www.zf.com/contact

1/19

Revision Date: 12.12.2018

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

2. Hazards identification

2.1 NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS

Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001. Not classified as Dangerous Goods for transport, according to NZS 5433:2012 Transport of Dangerous Goods on Land.

2.2 Hazard classification

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

2.3 GHS Label elements

Labelling

Hazard pictograms: No Hazard Symbol required

Signal word: No signal word

Hazard statements

PHYSICAL HAZARDS: Not classified as a physical hazard under

GHS criteria.

HEALTH HAZARDS: Not classified as a health hazard under

GHS criteria.

ENVIRONMENTAL HAZARDS: Not classified as environmental hazard

under GHS criteria.

Precautionary statements:

Prevention:No precautionary phrases.

Response: No precautionary phrases.

Storage: No precautionary phrases.

Disposal: No precautionary phrases.

Sensitising components: Contains alkyl acetamide.

Contains calcium sulphonate. May produce an allergic reaction.

2.4 Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of

© ZF Friedrichshafen AG Revision Date: 12.12.2018

Phone: +49 9721 4756-0 www.zf.com/contact

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

ZF Aftermarket

the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

Not classified as flammable but will burn.

3. Composition/information on ingredients

3.2 **Mixtures**

Synthetic base oil and additives. Chemical nature

Highly refined mineral oil.

The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.

* contains one or more of the following

CAS-numbers:

64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5,

848301-69-9.

Hazardous components

Chemical name	CAS-No.	Classification	Concentration [%]
Alkyl acetamid	Not Assigned	Skin Sens.1B; H317	1 - 3
Calcium sulphonate	Not Assigned	Skin Sens.1B; H317	0,1 - 0,9
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox. 1; H304	0 - 90

For explanation of abbreviations see section 16.

4. First aid measures

4.1 **Description of first aid measures**

General advice: Not expected to be a health hazard when

used under normal conditions.

Protection of first-aiders: When administering first aid, ensure that

you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

If inhaled: No treatment necessary under normal

conditions of use.

If symptoms persist, obtain medical advice.

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany Phone: +49 9721 4756-0

www.zf.com/contact

© ZF Friedrichshafen AG Revision Date: 12.12.2018

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

7F Aftermarket

In case of skin contact: Remove contaminated clothing. Flush ex-

posed area with water and follow by wash-

ing with soap if available.

If persistent irritation occurs, obtain medi-

cal attention.

In case of eye contact: Flush eye with copious quantities of water.

If persistent irritation occurs, obtain medi-

cal attention.

If swallowed: In general no treatment is necessary unless

large quantities are swallowed, however,

get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: Oil acne/folliculitis signs and symptoms

> may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting

and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Notes to doctor/physician:

Treat symptomatically.

5. Firefighting measures

5.1 **Extinguishing media**

> Suitable extinguishing media: Foam, water spray or fog. Dry chemical

> > powder, carbon dioxide, sand or earth may

be used for small fires only.

Unsuitable extinguishing media: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

> Specific hazards during firefighting: Hazardous combustion products may in-

> > clude: A complex mixture of airborne solid

and liquid particulates and gases (smoke). Carbon monoxide may be

Unidentified organic and inorganic

evolved if incomplete combustion occurs.

compounds.

ZF Friedrichshafen AG • ZF Aftermarket © ZF Friedrichshafen AG Revision Date: 12.12.2018

Phone: +49 9721 4756-0

Obere Weiden 12, 97424 Schweinfurt, Germany

www.zf.com/contact 4/19

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

5.3 Advice for firefighters

Special protective equipment for firefighters: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards

(e.g. Europe: EN469).

Specific extinguishing methods: Use extinguishing measures that are ap-

propriate to local circumstances and the

surrounding environment.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: For non emergency personnel:

Avoid contact with skin and eyes.

Emergency responders: For emergency responders:

Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions: Use appropriate containment to avoid envi-

ronmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appro-

priate barriers.

Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and materials for containment and cleaning up

Methods for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean

up immediately.

Prevent from spreading by making a barrier with sand, earth or other containment ma-

terial.

Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and

dispose of properly

AG • ZF Aftermarket © ZF Friedrichshafen AG Revision Date: 12.12.2018

www.zf.com/contact

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

7. Handling and storage

General Precautions:

Use local exhaust ventilation if there is risk

of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and dispos-

al of this material.

7.1 Precautions for safe handling

Advice on safe handling: Avoid prolonged or repeated contact with

skin.

Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper han-

dling equipment should be used.

Properly dispose of any contaminated rags or cleaning materials in order to prevent

fires.

Product Transfer: This material has the potential to be a stat-

ic accumulator.

Proper grounding and bonding procedures should be used during all bulk transfer op-

erations.

Avoidance of contact: Strong oxidising agents

7.2 Conditions for safe storage, including any incompatibilities

Other data: Keep container tightly closed and in a cool,

well-ventilated place.

Use properly labeled and closable contain-

ers. Store at ambient temperature.

Packaging material: Suitable material: For containers or con-

Phone: +49 9721 4756-0 www.zf.com/contact

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

ZF Aftermarket

tainer linings, use mild steel or high density

polyethylene.

Unsuitable material: PVC.

Container Advice: Polyethylene containers should not be ex-

posed to high temperatures because of

possible risk of distortion.

8. Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mine-	Not	WES-TWA (Mist)	5 mg/m³	NZ OEL
ral	Assigned			
	Further information: Sampled by a method that does not collect vapour.			
Oil mist, mine- ral	Not Assigned	WES-STEL (Mist)	10 mg/m ³	NZ OEL
Oil mist, mine- ral	Not Assigned	TWA (Mist)	5 mg/m³	OSHA Z-1
Oil mist, mine- ral	Not Assigned	TWA (Inhalable fraction)	5 mg/m³	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany © ZF Friedrichshafen AG Revision Date: 12.12.2018

Phone: +49 9721 4756-0 www.zf.com/contact 7/19

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

ZF Aftermarket

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping

8.3 Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection:

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

© ZF Friedrichshafen AG Revision Date: 12.12.2018

Phone: +49 9721 4756-0 www.zf.com/contact

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

ZF Aftermarket

Hand protection:

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection:

Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.

Respiratory protection:

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering

ZF Friedrichshafen AG • ZF Aftermarket
Obere Weiden 12, 97424 Schweinfurt, Germany

© ZF Friedrichshafen AG Revision Date: 12.12.2018

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

7F Aftermarket

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask

controls do not maintain airborne

and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

Thermal hazards: Not applicable

Environmental exposure controls

General advice: Take appropriate measures to fulfill the

requirements of relevant environmental

protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid at room temperatur

Colour: Green

Odour: Slight hydrocarbon

Odour Threshold: Data not available

pH: Not applicable

© ZF Friedrichshafen AG Revision Date: 12.12.2018

www.zf.com/contact

SAFETY DATA SHEET
The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

ZF Aftermarket

Pour point	-42° C / -44° F	ASTM D97	
Initial boiling point and boiling range	> 280° C / 536° F	estimated value(s)	
Flash point	206 °C / 403 °F	ASTM D92 (COC)	
Evaporation rate	Data not available		
Flammability (solid, gas)	Data not available		
Upper explosion limit	Typical 10 %(V)		
Lower explosion limit	Typical 1 %(V)		
Vapour pressure	< 0,5 Pa (20° C / 68° F)	estimated value(s)	
Relative vapour density	> 1	estimated value(s)	
Relative density	0,846 (15° C / 59° F)		
Density	846 kg/m³ (15° C / 59° F)	ISO 12185	
Solubility(ies)			
Water solubility	negligible		
Solubility in other solvents	Data not available		
Partition coefficient: n- octanol/water	Pow: > 6	based on infor- mation on similar products	
Auto-ignition temperature	> 320° C / 608° F	3° F	
Viscosity, dynamic	Data not available		
Viscosity, kinematic	26 mm²/s (40° C / 104° F) 5,6 mm²/s (100° C / 212° F)	ASTM D445	

Revision Date: 12.12.2018

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

ZF Aftermarket

Explosive properties	Not classified	
Oxidizing properties	Data not available	

9.2 Other information

Conductivity: This material is not expected to be a static

accumulator.

Decomposition temperature: Data not available

10. Stability and reactivity

10.1 Reactivity The product does not pose any further re-

activity hazards in addition to those listed

in the following subparagraph.

10.2 Chemical stability: Stable.

10.3 Possibility of hazardous reactions: Reacts with strong oxidising agents.

10.4 Conditions to avoid: Extremes of temperature and direct sun-

light

10.5 Incompatible materials: Strong oxidising agents.

10.6 Hazardous decomposition products: Hazardous decomposition products are not

expected to form during normal storage.

11. Toxicological information

11.1 Information on toxicological effects

Basis for assessment: Information given is based on data on the

components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individ-

ual component(s).

Information on likely routes of expo-

sure

Skin and eye contact are the primary routes of exposure although exposure may

occur following accidental ingestion.

Phone: +49 9721 4756-0 www.zf.com/contact

© ZF Friedrichshafen AG Revision Date: 12.12.2018

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

Acute toxicity

Product:

Acute oral toxicity: LD50 rat: > 5.000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification

criteria are not met.

Acute inhalation toxicity: Remarks: Based on available data, the

classification criteria are not met.

Acute dermal toxicity: LD50 Rabbit: > 5.000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification

criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye. Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

Components:

Alkyl acetamide:

Remarks: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation. May cause an allergic skin reaction in sensitive individuals.

Calcium sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Chronic toxicity

Germ cell mutagenicity

Product:

Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

ZF Friedrichshafen AG • ZF Aftermarket © ZF Friedrichshafen AG Revision Date: 12.12.2018 Obere Weiden 12, 97424 Schweinfurt, Germany

Phone: +49 9721 4756-0 www.zf.com/contact

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

Carcinogenicity

Product:

Remarks: Not a carcinogen. Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification

Other Carcinogenicity Classification:

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant. Does not impair fertility. Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. Ecological information

12.1 Ecotoxicity

Basis for assessment:

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is

and a second sec

representative of the product as a whole,

Phone: +49 9721 4756-0 www.zf.com/contact

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

7F Aftermarket

rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to

prepare aqueous test extract).

Product:

Toxicity to fish (Acute toxicity):

Remarks: Expected to be practically non toxic. Based on available data, the classification criteria are not met.: LL/EL/IL50 >

100 mg/l

Toxicity to crustacean (Acute toxicity)

Remarks: Expected to be practically non toxic. Based on available data, the classification criteria are not met. LL/EL/IL50 >

100 mg/l

Toxicity to algae/aquatic plants (Acute

toxicity)

Remarks: Expected to be practically non toxic. Based on available data, the classification criteria are not met. LL/EL/IL50 >

100 mg/l

Toxicity to fish (Chronic toxicity)

Remarks: Data not available

Toxicity to crustacean (Chronic

toxicity)

Remarks: Data not available

Toxicity to microorganisms

(Acute toxicity)

Remarks: Data not available

12.2 Persistence and degradability

Product:

Biodegradability

Remarks: Not readily biodegradable. Major constituents are inherently biodegradable,

but contains components that may

persist in the environment.

Bioaccumulative potential 12.3

Bioakkumulation

Product:

Remarks: Contains components with the

potential to bioaccumulate.

Partition coefficient: n-octanol/water

Pow: > 6 Remarks: (based on information

on similar products)

12.4 Mobility in soil

> Product: Mobility

Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to

soil particles and will not be mobile.

Remarks: Floats on water.

Other adverse effects

ZF Friedrichshafen AG • ZF Aftermarket © ZF Friedrichshafen AG Revision Date: 12.12.2018 Obere Weiden 12, 97424 Schweinfurt, Germany

Phone: +49 9721 4756-0

www.zf.com/contact 15/19

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

7F Aftermarket

Product:

Additional ecological information

Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential. Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use. Poorly soluble mixture. Causes physical fouling of aquatic organisms.

13. **Disposal considerations**

Waste treatment methods 13.1

Waste from residues:

Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with

applicable regulations.

Do not dispose into the environment, in

drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous

waste.

Contaminated packaging: Dispose in accordance with prevailing reg-

> ulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local legislation Remarks Disposal should be in accordance with ap-

plicable regional, national, and local laws

and regulations.

14 **Transport information**

14.1 **National Regulations**

www.zf.com/contact

Land Transport Rule: Not regulated as a dangerous good Dangerous Goods 2012 - NZS 5433

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany Phone: +49 9721 4756-0

© ZF Friedrichshafen AG Revision Date: 12.12.2018

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

14.2 International Regulation

IMDG-Code Not regulated as a dangerous good IATA-DGR Not regulated as a dangerous good

14.3 Special precautions for user

Remarks: Special Precautions: Refer to Chapter 7,

Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with

transport.

14.4 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category:
Ship type:
Not applicable
Product name:
Not applicable
Not applicable
Not applicable
Not applicable

Additional Information: MARPOL Annex 1 rules apply for bulk

shipments by sea.

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

R-phrase(s): Not classified. S-phrase(s): Not classified.

New Zealand Workplace Exposure Limits 2002 (WES). New Zealand Standard 5433:2012

Transport of Dangerous Goods on Land.

Other international regulations:

The components of this product are reported in the following inventories:

EINECS/ELINCS/EC: All components listed or polymer exempt.

TSCA: All components listed.

16. Other information

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

ZF Friedrichshafen AG • ZF Aftermarket Obere Weiden 12, 97424 Schweinfurt, Germany

Phone: +49 9721 4756-0 www.zf.com/contact © ZF Friedrichshafen AG Revision Date: 12.12.2018

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



ZF Aftermarket

Trade name: ZF-LIFEGUARDFLUID 8

Full text of other abbreviations

Asp. Tox. Aspiration hazard Skin Sens. Skin sensitisation

Abbreviations and Acronyms:

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR -Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD- Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN -United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

Further information

Training advice: Provide adequate information, instruction and training for operators.

narket © ZF Friedrichshafen AG Revision Date: 12.12.2018

www.zf.com/contact

The content and format of this SDS is in accordance with HSNO ApprovedCode of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.



Trade name: ZF-LIFEGUARDFLUID 8

ZF Aftermarket

Other information: A vertical bar (|) in the left margin indicates

an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet:

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

© ZF Friedrichshafen AG Revision Date: 12.12.2018

19/19

www.zf.com/contact