

1. Product and company identification

1.1 Product identifier

Product name:

Product number:

5961.308.591

ZF LifeguardFluid 7.4 DCT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses:	Hydraulic/transmission fluid
Uses advised against:	No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

ZF Friedrichshafen AG ZF Aftermarket Obere Weiden 12 97424 Schweinfurt Germany +49 9721 475 60 www.zf.com /contact

1.4 Emergency number 24/7h Emergency information/ emergency number: (+49) 89 19 240 (Poison emergency call – Information in German and English)

2. Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

Health Hazards Carcinogenicity

Category 2

Hazard summary Physical Hazards:

l Hazards:

No data available.

2.2 Label Elements

Signal Words:

Warning





ZF Aftermarket

Hazard Statement(s):	H351: Suspected of causing cancer. H412: Harmful to aquatic life with long lasting effects.
Precautionary Statements	
Prevention:	 P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P281: Use personal protective equipment as required. P273: Avoid release to the environment.
Response:	P308+P313: IF exposed or concerned: Get medical advice/attention.
Storage:	P405: Store locked up.

2.3 Other hazards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Unknown toxicity:

Due to information available product does not contain any ingredients of unknown toxicity.

3. Composition/ Information on ingredients

General information:

Mixture containing severely refined base oils and additives.

Chemical name	Identifier	Concentratio n *	Notes
base oil, low viscous	72623-87-1	50,00 - <100,00%	
Base oil paraffinic	64742-54-7	1.00 - <5.00%	
hydrocarbons, low viscous	64742-94-5	0.10 - <1.00%	

© ZF Friedrichshafen AG

status: 17.05.2024



Product name: ZF LifeguardFluid 7.4 DCT

ZF Aftermarket

Alkyl amine	61791-44-4	0,10 -	
		<0,25%	
prim.	218141-16-3	0,01 -	
alkanolamine		<0,10%	
ether			

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Classification		
Chemical name	Identifier	Classification
base oil, low	72623-87-1	Asp. Tox. 1;H304
viscous		
Base oil	64742-54-7	Asp. Tox. 1;H304
paraffinic		
hydrocarbons,	64742-94-5	Carc. 2;H351, Asp. Tox. 1;H304,
low viscous		STOT SE 3;H336, Aquatic Chronic
		2;H411
Alkyl amine	61791-44-4	Skin Corr. 1C;H314, Eye Dam.
		1;H318, Aquatic Acute
		1;H400, Aquatic Chronic 1;H410,
		Acute Tox. 4;H302; M-Factor
		(aquatic acute): 10; M-Factor
		(aquatic chronic): 1
prim.	218141-16-3	Acute Tox. 4;H302, Skin Corr.
alkanolamine		1B;H314, Eye Dam. 1;H318,
ether		Aquatic Acute 1;H400, Aquatic
		Chronic 1;H410; M-Factor
		(aquatic acute): 100; M-Factor
		(aquatic chronic): 1

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

4. First aid measures General:

Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation:

Supply fresh air; consult doctor in case of symptoms.

© ZF Friedrichshafen AG

Product name: ZF LifeguardFluid 7.4 DCT



Eye contact:	Promptly wash eyes with plenty of water while lifting the eye lids.
Skin Contact:	Wash with soap and water.
Ingestion:	Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed

May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if symptoms occur.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:	CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added
Unsuitable extinguishing media:	Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire fighting procedures:	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
Special protective equipment for fire- fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.



6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures In case of spills, beware of slippery floors and surfaces.

6.2 Environmental Precautions

Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

7. Handling and storage

7.1 Precautions for safe handling

Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities

Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.

7.3 Specific end use(s)

No data available.

8. Exposure controls/ personal protection

8.1 Exposure Limits

Chemical name	Туре	Exposure	Source
		Limit Values	



Product name: ZF LifeguardFluid 7.4 DCT

base oil, low viscous - Inhalable fraction	TWA	5 mg/m³	US. ACGIH Threshold Limit Values, as amended (03 2014)
base oil, low viscous	PEL	500 ppm 2,000 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
base oil, low viscous - Mist.	PEL	5 mg/m³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
base oil, low viscous	TWA	400 ppm 1,600 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
base oil, low viscous - Mist.	TWA	5 mg/m³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:	Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to inhandling the chemicals or the mineral oil products.
Eye/face protection:	Safety glasses (EN 166)

Safety glasses (EN 166) recommended during refilling. Avoid contact with skin and eyes.

Product name: ZF LifeguardFluid 7.4 DCT



	Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.
Skin protection Hand Protection:	Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: >= 480 min Recommended thickness of the material: >= 0.38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
Respiratory Protection:	Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.
Thermal hazards:	No data available.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Product name: ZF LifeguardFluid 7.4 DCT



Appearance Physical state: Color: Odor: Odor Threshold: pH: Freezing point: **Boiling Point:** Flash Point: **Evaporation Rate:** Flammability (solid, gas): Flammability Limit - Upper (%)-: Flammability Limit - Lower (%)-: Vapor pressure: Vapor density (air=1): Density: Solubility(ies) Solubility in Water: Solubility (other): Partition coefficient (n-octanol/water): Autoignition Temperature: **Decomposition Temperature:** Kinematic viscosity: Explosive properties: Oxidizing properties:

liquid Amber Characteristic Not applicable for mixtures Not applicable Not applicable for mixtures Value not relevant for classification > 200 °C Not applicable for mixtures Value not relevant for classification Not applicable for mixtures 0.83 - 0.85 g/cm³ (15 °C)

Insoluble in water No data available. Not applicable for mixtures Value not relevant for classification Value not relevant for classification 33 - 37 mm²/s (40 °C) Value not relevant for classification Value not relevant for classification

9.2 Other information No data available.

10. Stability and reactivity 10.1 Reactivity Stable under normal use conditions. 10.2 Stable under normal use conditions. **Chemical Stability** 10.3 Possibility of hazardous reactions Stable under normal use conditions. 10.4 Conditions to avoid Stable under normal use conditions. 10.5 **Incompatible Materials** Strong oxidizing substances. Strong acids. Strong bases. 10.6 **Hazardous Decomposition** Thermal decomposition or combustion Products may liberate carbon oxides and

© ZF Friedrichshafen AG



other toxic gases or vapors.

11. Toxicological information

11.1 Information on likely routes of exposure

Inhalation: Ingestion: Skin Contact: Eye contact:

Acute toxicity

Oral Product: Specified substance(s) base oil, low viscous

Base oil paraffinic hydrocarbons, low viscous Alkyl amine Dermal Product: Specified substance(s) base oil, low viscous

Inhalation Product:

Specified substance(s) Base oil paraffinic

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

Base oil paraffinic Alkyl amine OECD 404 Not irritant. OECD 404 (Rabbit, 14 d): Causes severe skin burns.

Serious Eye Damage/Eye Irritation: Product: Based on available data, the

classification criteria are not met.

No data available. No data available. No data available.

No data available.

Not classified for acute toxicity based on available data. LD 50 (Rat): > 5,000 mg/kg (OECD 401)

LD 50 (Rat): > 5,000 mg/kg LD 50 (Rat): 6,318 mg/kg (OECD 423) LD 50 (Rat): 1,350 mg/kg (OECD 401) Not classified for acute toxicity based on available data. LD 50 (Rabbit): > 31,600 mg/kg

Not classified for acute toxicity based on available data.

LC 50 (Rat, 4 h): > 5.53 mg/l Not classified for acute toxicity based on available data.





Specified substance(s)
Base oil paraffinicOECD 405 Not irritant.Respiratory or Skin Sensitization
Product:Skin sensitizer: Based on available
data, the classification criteria are not
met.
Respiratory sensitizer: Based on
available data, the classification

Specified substance(s) Alkyl amine

No sensitizing effect (guinea pig); OECD 406

criteria are not met.

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity Product:

Based on available data, the classification criteria are met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHASP: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure Product:

Based on available data, the classification criteria are not met.

Aspiration Hazard

Product:



Based on available data, the classification criteria are not met. **Specified substance(s)** Base oil paraffinic May be fatal if swallowed and enters airways.

12. Ecological information

12.1 Toxicity

Acute toxicity Product:

Fish Specified substance(s) Alkyl amine Base oil paraffinic hydrocarbons, low viscous

Aquatic Invertebrates Specified substance(s) Base oil paraffinic Alkyl amine

base oil, low viscous

Chronic Toxicity Product:

Fish Specified substance(s) base oil, low viscous

Aquatic Invertebrates Specified substance(s) base oil, low viscous Alkyl amine

Base oil paraffinic

Toxicity to Aquatic Plants Specified substance(s) base oil, low viscous Alkyl amine Based on available data, the classification criteria are not met.

LC 50 (Fish, 96 h): 0.1 mg/l (OECD 203)

LC 50 (Fish, 96 h): > 100 mg/l LC 50 (Fish, 96 h): 2 - 5 mg/l

EC 50 (Water Flea, 48 h): > 100 mg/l EC 50 (Water Flea, 48 h): 0.043 mg/l (OECD 202) EL50 (Water Flea, 48 h): > 10,000 mg/l (OECD 202)

Based on available data, the classification criteria are met.

NOEC (Fish, 14 d): > 1,000 mg/l

NOEC (Water Flea, 21 d): 10 mg/l (OECD 211)

EC 10 (Water Flea, 21 d): 0.0107 mg/l (OECD 211) NOEC (Daphnia magna, 21 d): 10 mg/l (OECD 211)

NOEC (Alga, 72 h): > 100 mg/l (OECD 201)

EC 50 (Alga, 72 h): 0.0538 mg/l (OECD 201) NOEC (Alga, 72 h): 0.0156 mg/l

© ZF Friedrichshafen AG

status: 17.05.2024

Base oil paraffinic

Biodegradation

Product:

Alkyl amine

Product name: ZF LifeguardFluid 7.4 DCT

hydrocarbons, low viscous

Persistence and Degradability

ZF Aftermarket

Specified substance(s)

hydrocarbons, low viscous

- **12.3 Bioaccumulative potential** Product:
- **12.4 Mobility in soil** Product:

12.2

EC 50 (Algae, 72 h): > 100 mg/l (OECD 201) EC 50 (Alga, 72 h): 1 - 3 mg/l (OECD 201)

Not applicable for mixtures

63 % (28 d, OECD 301D) Readily biodegradable

58 % (28 d)

Not applicable for mixtures

Not applicable for mixtures

12.5 Results of PBT and vPvB assessment The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects No data available.

13. Disposal considerations

13.1 Waste treatment methods

General information:

Disposal methods:

Dispose in accordance with all applicable regulations.

Discharge, treatment, or disposal may be subject to national, state, or local laws.

14. Transport information

DOT

www.zf.com/contact

Not regulated.

IMDG - International Maritime Dangerous Goods Code

Not regulated.



ZF Aftermarket

IATA

Not regulated.

15. Regulatory information

US Federal Regulations

US State Regulations

US. California Proposition 65

WARNING! This product can expose you to chemicals including

NAPHTHALENE	which is [are] known to the State of
	California to cause cancer

For more information go to www.P65Warnings.ca.gov.

Inventory Status

DSL	On or in compliance with the inventory
TSCA	On or in compliance with the inventory

16. Other information

Revision Information:

Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product

Product name: ZF LifeguardFluid 7.4 DCT



ZF Aftermarket

only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.